

# SUPPORT ACCESSORIES CASTERS

CASTER	CODE/CAPACITY PER PAIR	CASTER	CODE/CAPACITY PER PAIR
4" DIA. RUBBER RIGID	4RR/600 lbs.	4" DIA. RUBBER SWIVEL W/TOE BRAKE	4RSB/-
4" DIA. STEEL RIGID	4SR/700 lbs.	6" DIA. RUBBER RIGID	6RR/1120 lbs.
4" DIA. V-GROOVE RIGID	4VR/-	6" DIA. STEEL RIGID	6SR/1150 lbs.
4" DIA. RUBBER SWIVEL	4RS/600 lbs.	6" DIA. RUBBER SWIVEL	6RS/1120 lbs.
4" DIA. STEEL SWIVEL	4SS/700 lbs.	6" DIA. STEEL SWIVEL	6SS/1150 lbs.
4" DIA. V-GROOVE SWIVEL	4VS/-	6" DIA. STEEL SWIVEL W/BRAKE	6SSB/-
FLOORLOCK FOR 4" CASTER	-	FLOORLOCK FOR 6" CASTER	-

## CASTERS FOR LIGHT DUTY CONVEYORS SLC-5-16-4SRBF

SLC-(elevation code)-(between frames\*)-(caster model\*\*)-(floorlock@)

\*Specify 10", 16" or 22" between frames only. Model SLC is suited specifically for wheel conveyors and 138 gravity series.

\*\*See chart for caster model number.

@Specify F if floorlock required.

## CASTERS FOR MEDIUM DUTY CONVEY-

ORS

SMC-4-13-4RSBF

S (medium or heavy duty\*) C-(elevation code)-(between frames)-(caster model\*\*)-(floorlock@)

\*Specify M for medium duty supports and H for heavy duty supports.

\*\*See chart for caster model number.

@Specify F if floorlock required.

### SPECIFICATIONS

CASTERS: 4" dia. or 6" dia., steel or rubber, swivel or rigid, V-groove casters; floor locks, wheel brakes available. Two casters supplied per support with enlarged mounting plate welded to legs.

CAPACITY: Up to 1150 lb. caster capacity. Consult factory for heavy duty casters.

OPTIONAL: Angle track for V-groove.



■ 24 hour shipment

■ 2 week shipment