

# GRAVITY BUTT SPURS

## WHEEL AND 1-3/8" DIA. X 18 GA. GALV. ROLLER BUTT SPURS



Roach gravity roller butt spurs divert flow of goods at 30° or 45°, right or left and 90° by simply adding a standard 45° curve to spur.

### SPECIFICATIONS

**ROLLERS:** 1-3/8" x 18 ga. galvanized steel roller, model 138G, on model BSR.

**WHEELS:** 1-15/16" dia. prelubricated ball bearing wheel with hardened raceway, zinc plated on model BSW.

**FRAMES:** Formed galvanized steel channel 2-1/2" x 1" x 12 ga.; supplied with hook and rod coupling.

### ROLLER BUTT SPURS MODEL NUMBER

**BSR-12-1.5-30-R**

BSR-(overall width\*)-(roller centers\*\*)-(degree@)-(left or right hand#)

\*Specify 12", 18" or 24" OAW.

\*\*Specify 1.5" or 3" roller centers. NOTE: 2 week shipment on models with 1.5" roller centers.

@Specify 30° or 45°.

#See page 8 to determine hand of spur.

### WHEEL BUTT SPURS MODEL NUMBER

**BSW-12-30-R**

BSW-(overall width\*)-(degree@)-(left or right hand#)

\*Specify 12", 18" or 24" OAW.

@Specify 30° or 45°.

#See page 8 to determine hand of spur.

■ 24 hour shipment ■ 2 week shipment

## 1.9" DIA. X 16 GA. STEEL ROLLER BUTT SPURS



Roach gravity roller butt spurs divert flow of goods at 30° or 45°, right or left and 90° by simply adding a standard 45° curve to spur.

### SPECIFICATIONS

**ROLLERS:** 1.9" x 16 ga. steel, model 196S.

**FRAMES:** Formed steel channel, 3-1/2" x 1-1/2" x 10 ga.; 13", 15", 17", 19", 21", 23", 25", 27", 31", 33", 37", 39", 43", 47" and 51" BF available.

**ROLLER CENTERS:** Model RBS furnished with 3" roller centers.

**BEARINGS:** Integral plain ball bearings, zinc plated, grease packed.

### 1.9" ROLLER BUTT SPURS MODEL NUMBER

**RBS-13-30-R**

RBS-(between frames)-(degree@)-(left or right hand#)

@Specify 30° or 45°.

#See page 8 to determine hand of spur.