PRODUCT STOPS ANGLE AND ROLLER STOPS



Both angle and roller stops serve as an economical means to stopping goods at a given fixed point. "BR" brackets or angle stop quickly attaches to conveyor frame top flange.

ANGLE STOPS MODEL NUMBER ASM-33

AS (light, medium or heavy duty*)-(between frames**)
*Specify L for light duty, M for medium duty or H for heavy duty.

**Specify OAW for model ASL, available in 12", 18" and 24" OAW only and is suited specifically for wheel conveyors and 138 gravity series.

ROLLER STOPS MODEL NUMBER BR-196S-21

BR-(roller type*)-(between frames)
*Specify 138G, 196S, 196G, 192S, 199S, 254S, 251S
or 297S.

SPECIFICATIONS

ANGLE STOP: Model ASL for light duty and ASM for medium duty applications $(1-1/2" \times 1-1/2" \times 10 \text{ ga.})$; Model ASH for heavy duty applications $(1-1/2" \times 1-1/2" \times 7 \text{ ga.})$.

ROLLER STOP: Includes pair of brackets and roller as specified in model number.

WIDTHS: Medium and heavy duty 24 hour shipments include 13", 15", 17", 19", 21", 23", 25", 27", 31", 33", 37", 39", 43", 45", 47" and 51" BF; light duty available in 12", 18" and 24" OAW.



■ 24 hour shipment

