


SUPPORTS

LIGHT DUTY TRIPOD SUPPORTS



Tripod supports are the choice for fast set-up or temporary installations. Easily adjustable, tripods are designed for wheel conveyors and 138 gravity series roller conveyors. Tripods are simply placed underneath conveyor section crossbrace as shown in detail at right.



SPECIFY MODEL NUMBER FOR TRIPODS
T-18-40

T-(overall width*)-(elevation code)

*Specify 12", 18" or 24" overall width only. Tripods are suited specifically for wheel conveyors and 138 gravity series conveyors ONLY.

SPECIFICATIONS

CONSTRUCTION: Top channel of tripod is 1-9/16" x 15/16" x 12 ga. welded to 1" inside diameter pipe. Tripod base is 12 ga. construction.

ELEVATION CODE	HEIGHT ADJUSTMENT MIN. (TOP OF TRIPOD)	HEIGHT ADJUSTMENT MAX. (TOP OF TRIPOD)	12" OAW WT. (lbs.)	18" OAW WT. (lbs.)	24" OAW WT. (lbs.)
18	9-1/4"	15-1/4"	8	9	10
30	15-1/4"	27-1/4"	11	12	13
40	21-1/4"	37-1/4"	13	14	15
52	27-1/4"	49-1/4"	15	16	17
72	37-1/4"	69-1/4"	18	19	20
110	57-1/4"	107-1/4"	25	26	27

■ 24 hour shipment