

SUPPORTS

MODEL SL LIGHT DUTY PERMANENT SUPPORTS



MODEL SL
1500 lbs. support capacity

SPECIFICATIONS

CONSTRUCTION: 12 ga. inside and outside channel assemblies; C-3 plates are 10 ga.; cross braces are 10 ga. up to 27" BF and 7 ga. 31" BF and above.

WIDTHS: 24 HR shipments include SL in 10", 16" & 22" BF ONLY.

LIGHT DUTY SUPPORTS MODEL NUMBER
SL-6-10

SL-(elevation code)-(between frames*)

*Specify 10", 16" or 22" between frames which is available for 12", 18" and 24" OAW conveyors ONLY and is suited specifically for wheel conveyors and 138 gravity series.

ELEVATION CODE	HEIGHT ADJUSTMENT MIN. (TOP OF SUPPORT)	HEIGHT ADJUSTMENT MAX. (TOP OF SUPPORT)	10"-22" BF WEIGHT (lbs.)
1	7-1/4"	10-1/4"	11
2	10-1/4"	13-1/4"	13
3	13-1/4"	16-1/4"	15
4	16-1/4"	22-1/4"	17
5	20-1/4"	26-1/4"	22
6	24-1/4"	36-1/4"	24
7	34-1/4"	46-1/4"	28
8	46-1/4"	58-1/4"	35
9	58-1/4"	70-1/4"	39
10	70-1/4"	82-1/4"	43
11	80-1/4"	92-1/4"	47
12	92-1/4"	104-1/4"	51

■ 24 hour shipment